

Support Vector Machine (SVM) Documentation

Description: Classify samples using SVM

Author: Joshua Gould, gp-help@broad.mit.edu

Summary: The Support Vector Machines (SVM) module implements the support vector machines algorithm for supervised classification methods to compute a maximal separating hyperplane between the expression vectors of different classes or phenotypes. Given microarray data with n genes per sample, SVM outputs a hyperplane, w, which can be thought of as a vector with n components each corresponding to the expression of a particular gene. Loosely speaking, assuming that the expression values of each gene have similar ranges, the absolute magnitude of each element in w determines its importance in classifying a sample, since.

$$f(x) = \sum_{i=1}^{n} w_i x_i + b ,$$

and the class label is sign[f(x)].

The SVM model can be tested on a separately specified test set. Additionally, the model can be saved and used subsequently on additional test sets.

The table below summarizes the different options available and which parameters are required depending on the option selected.

| Parameter | Train | Test with saved model | Train/Test |
|----------------------|------------------|------------------------|--------------------------|
| | create a | run a saved model on a | create a model on |
| | predictive model | new test dataset | training data and run it |
| | from a training | | on test data |
| | dataset | | |
| train.data,filename | Required | No | Required |
| train.cls.filename | Required | No | Required |
| saved.model.filename | No | Required | No |
| test.data.filename | No | Required | Required |
| test.cls.filename | No | Required | Required |
| pred.results.file | No | Yes | Yes |
| model.output.file | Required | No | Required |

References:

- R. Rifkin, S. Mukherjee, P. Tamayo, S. Ramaswamy, C-H Yeang, M. Angelo, M. Reich, T. Poggio, E.S. Lander, T.R. Golub, J.P. Mesirov, An Analytical Method for Multiclass Molecular Cancer Classification, SIAM Review, 45:4, (2003).
- T. Evgeniou, M. Pontil, T. Poggio, *Regularization networks and support vector machines*, Adv. Comput. Math., 13 (2000), pp. 1-50.
- V. Vapnik, Statistical Learning Theory, Wiley, New York, 1998.

GerePattern

Parameters:

| Name | Description |
|----------------------|--|
| train.data.filename | The training data filegct, .res |
| train.cls.filename | The training class filecls |
| saved.model.filename | A saved model from a previous run of SVM |
| test.data.filename | The test data filegct, .res |
| test.cls.filename | The test class filecls |
| pred.results.file | The name of the output file for prediction results |
| model.output.file | The name of the file containing the saved model |

Output Files:

If test data is supplied:

1. file containing the prediction results If training data is specified

1. a file containing the saved prediction model

Platform dependencies:

Module type: Prediction

CPU type: any Language: R